



Belgium / English

Zoeken

Live chat

maandag tot vrijdag

+31 33 4545600

Home | Producten | Markten | Ondersteuning | Bedrijfsinformatie | Partners | Waar te koop

Related Products

- [StyleView® Cart with LCD Arm](#)
- [StyleView® Cart with LCD Arm, LiFe Powered](#)
- [StyleView® Cart with LCD Arm, 1 Drawer \(1x1\)](#)
- [StyleView® Cart with LCD Arm, LiFe Powered, 2 Drawers \(1x2\)](#)
- [StyleView® Transfer Cart](#)

**StyleView® Cart with LCD Arm, LiFe Powered, 2 Drawers (2x1)**

NEW

Stay productive and on the go with our LiFe powered computer cart. This innovative, truly ergonomic and easy-to-manuever healthcare cart features sit-to-stand height adjustment, side-to-side LCD and keyboard motion, bi-focal viewing and an adjustable back-tilt keyboard tray. Its auto-locking drawer system enables simple and efficient management of non-controlled medication.



G+1 < 0 Like < 0

Part Number: **SV44-12A2\***

[+ Accessories](#)  
[+ Services](#)

\* Part Number:  
SV44-12A2-1 = US/CA/MX  
SV44-12A2-2 = EU/SA  
SV44-12A2-3 = UK/IE/SA  
SV44-12A2-3 = HK/MY/SG  
SV44-12A2-4 = AU/NZ  
SV44-12A2-5 = CN  
SV44-12A2-B = IN  
SV44-12A2-C = CHE

\* Order part number that coincides with regional power system requirements.



**Don't leave your cart. Your way.**  
A portable, battery-powered cart that is easy to use, easy to store, and easy to move. It has a height-adjustable seat, a backrest, and a tray for your laptop or tablet. It also has a drawer for your medication. [Watch it now!](#)



< 1 2 3 4 >

Suggested Accessories



[+ More Accessories](#)

Benefits

- LiFe makes the cart extremely lightweight and easy to move
- Ultrafast recharge ensures caregiver and cart uptime: A full recharge from full discharge can be completed in about two hours
- Long battery 'LiFe' minimizes time and cost for maintenance and replacement
- For patient and caregiver safety the entire power system and the FULL cart are certified to UL/EN/IEC 60601-1. Complies with EMI limits of FCC Part 15 Class A
- Auto-locking drawer system: simple and efficient medication management at the point-of-care reduces opportunities for errors; security system stores variable-length PINs for up to 1,000 users with StyleLink software (100 users without StyleLink)
- Drawer system supports "Pharmacy mode," allowing all drawers to be unlocked simultaneously to facilitate efficient stocking of medication
- Extra rows of drawers may be added—up to a maximum of 5 rows
- Truly ergonomic design accommodates the largest range of nurses and other caregivers; designed for sitting or standing with single-motion fluid adjustment—helps promote caregiver wellness and productivity
- StyleView's small footprint, with ultra-smooth gliding casters, travels easily across crowded carpet or hard surface floors and is perfect for space constrained areas
- Open-architecture design accommodates multiple configurations: closed notebooks with monitor, CPU and monitor, thin clients, tablets, all-in-one computers and future hardware upgrades
- LCD and keyboard pan side-to-side for closer access while interacting with clients; arm also reaches low for people wearing bifocals or using a tablet PC
- Passes [Ergotron's 10,000-cycle motion test](#), which ensures years of trouble-free sit-to-stand height adjustment

Tech Specs

Screen	Capacity	Lift	Tilt	Pan	Rotation	VESA
≤ 24"	≤ 33 lbs* 15 kg	27"+ 68 cm	65°	180°	360° †	MIS-D

Part Numbers: North America = SV44-12A2-1; Europe/Saudi Arabia = SV44-12A2-2; United Kingdom/Ireland/Saudi Arabia = SV44-12A2-3; Hong Kong/Malaysia/Singapore = SV44-12A2-3; Australia/New Zealand = SV44-12A2-4; China = SV44-12A2-5; India = SV44-12A2-B; Switzerland = SV44-12A2-C

Description: StyleView Cart with LCD Arm, LiFe Powered, 2 Drawers (2 medium drawers x 1 row)

TAA (Trade Agreements Act) compliant

Includes auto-locking drawer system (ADS), primary double drawer, drawer dividers, LCD arm, worksurface, CPU lock, secure CPU compartment, four-port USB hub, scanner holder bracket, mouse holder, wrist rest, back-tilt keyboard tray, keyboard lights, left/right mouse tray, rear handle, storage basket, cable storage, four casters (lockable), single-battery 40 Ah LiFe power system, 10-foot (3 m) coiled cord, AC outlets, power system user interface, StyleLink software

\* Total maximum load on height-adjustment assembly = 33 lbs (15 kg). This is the sum of the following components: LCD pivot = 5-11 lbs (2.3-5 kg); worksurface ≤ 5 lbs (2.2 kg); keyboard tray ≤ 2 lbs (1 kg); CPU compartment ≤ 13 lbs (5.9 kg); medium drawer ≤ 1 lbs (.5 kg)

Note: If the combined LCD and CPU weight is greater than 23 lbs (10.4 kg) then the CPU must be mounted to the rear of the cart using the Universal CPU Holder accessory (ordered separately)

† LCD and worksurface adjust 20" (51 cm) in tandem; LCD Arm adjusts 7" (17 cm) independently; maximum LCD height adjustment = 27" (68 cm)

Quick Finder

Search by Display Type



— OR —

Search by Display Model

Select Manufacturer

— MORE FINDERS —

Stand Up Desks

SV Medical Carts

Charging Systems

† Portrait screen orientation may be incompatible with widescreen displays > 19"

Cart may be fitted with up to five rows of standard-height drawers. Vertical adjustment range is affected by the number of drawer rows: 0–2 rows = 20" (51 cm); 3 rows = 16" (41 cm); 4 rows = 12" (30 cm); 5 rows = 8" (20 cm)

Cart may be fitted with up to three rows of tall drawers

#### True Ergonomics

- Ergonomic back-tilt keyboard tray with left or right mouse tray ensures wrists remain in a neutral position during data entry—avoid repetitive-stress injuries while increasing comfort and productivity
- Designed for users 5'0" to 6'1" (152 to 185 cm) tall and for prolonged sitting or standing applications. The exceptional height adjustment range means shorter and taller users can work comfortably and productively in a seated as well as standing position
- Patented CF™ lift-and-pivot motion technology minimizes forces required to adjust cart position: Casters, height adjustment, LCD tilt and pan all require just a touch
- Arm adjusts screen down low to the worksurface for people wearing bifocals or using a tablet PC

#### Safe

- For patient and caregiver safety the entire power system and the FULL cart are certified to UL/EN/IEC 60601-1 and CAN/CSA-C22.2 No. 60601-1:08. Also complies with EMI limits of FCC Part 15 Class A
- Power System User Interface integrated conveniently on the worksurface (includes visual and audible battery status indicator)
- Surfaces are treated with antimicrobial for product protection; handles are smooth and continuous for improved cleanability
- Environmentally clean: RoHS, REACH, WEEE and EU (94/62/EC) packaging compliant
- Durable, easy-to-clean exterior composed of aluminum, high-grade plastic and zinc-plated steel promotes infection control
- Large, smooth worksurface; easy-to-clean design promotes infection control
- Lockable, ventilated enclosed storage for closed notebook, thin client or CPU. Keys and locks are heavy-duty
- Locking casters
- CPU lock provided inside the storage compartment for additional security
- Designed to meet guidelines established by the American National Standards Institute for computer use

#### Service

- Includes FREE StyleLink with enterprise capabilities: Install, access and manage your StyleView power systems from a remote location across WAN, LAN, or VPN
- Covered by Global Service Program—24/7 coverage

#### All the Details Covered

- Drawer dividers are included, allowing compartments to be customized to match your workflow requirements
- Four amber LEDs provide light over keyboard tray; includes 15-minute auto shut-off
- Button for LED lights is located conveniently on worksurface
- Rear basket keeps task-related items where they can be quickly accessed
- Universal mounting slot for accessories and equipment
- A unique cable management system conceals and organizes cords, making cleaning easy
- Ships fully assembled
- Quick, easy access to CPU storage compartment: One-hand operation of secure latch with slide-out worksurface ensures easy access. Security cable in compartment deters CPU theft
- Four-port USB hub
- Easy access to components for field replacement and serviceability: keyboard LEDs, PC boards (including the user interface). Easier, faster upkeep and service means less down time
- Pre-routed cables provide quicker integration with equipment
- Onboard power strip with three or two receptacles (country dependent)
- Four (4) ultra-smooth gliding casters for extremely easy push/pull mobility; locking casters ensure lock-in-place stability

#### Compatibility and Dimensions

- Internal Dimensions: medium drawer = 2.5"H x 5.5"W x 10.5"D (63.5 x 140 x 267 mm)—includes dividers to configure up to 4 compartments
- Open-architecture design accommodates multiple configurations, closed notebooks with monitor (even widescreen with up to 17.3" diagonal size), CPU and monitor, thin clients, tablets, all-in-one computers and future hardware upgrades
- Storage compartment for closed notebook, thin client or CPU: 17.75"W x 14.75"D x 4"H (45 x 37.5 x 10.1 cm); larger computers can mount to rear of cart with Universal CPU Holder accessory (ordered separately)
- Compact Wheel-to-Wheel Base Dimensions: 15.5" x 17" (394 x 432 mm)
- Worksurface Dimensions: 22.4"W x 19.75"D (567 x 502 mm)
- Mounting Standards: VESA FDMI MIS-D, 100/75, C (hole pattern: 100 x 100 mm & 75 x 75 mm)
- VAC:
  - SV44-12A2-1 = 120V/60Hz
  - SV44-12A2-2 = 230V/50Hz
  - SV44-12A2-3 = 230V/50Hz
  - SV44-12A2-4 = 230V/50Hz
  - SV44-12A2-5 = 220V/50Hz
  - SV44-12A2-B = 230V/50Hz/60Hz
  - SV44-12A2-C = 230V/50Hz
- Grounded Plug:
  - SV44-12A2-1 = NEMA 5-15P Hospital Grade
  - SV44-12A2-2 = European CEE 7
  - SV44-12A2-3 = UK BS 1363
  - SV44-12A2-4 = AS/NZS 3112
  - SV44-12A2-5 = GB2009-1, GB1002-1
  - SV44-12A2-B = BS 546
  - SV44-12A2-C = SEV 1011
- 40 Ah Power System with one (1) 40 Ah, 12 V DC, Lithium Iron Phosphate (LiFe) battery

Shipping Dimensions: 24.5"W x 34"D x 56"H (62 x 87 x 142 cm)

Shipping Weight: 158 lbs (71.7 kg); actual cart weight = 123 lbs (55.8 kg)

Warranty: Five (5) years for cart's mechanical components, two (2) years on power module; five (5) years on Life battery, including two-year capacity guarantee. See complete [warranty](#) for details

#### Support Material

<a href="#">StyleView Brochure</a>	English	pdf	4321 KB
<a href="#">Dimensional Illustrations</a>		pdf	3796 KB
<a href="#">Cleaning Instructions</a>	English	pdf	592 KB
<a href="#">Installation Manual</a>	English	pdf	5505 KB

<a href="#">Installation Manual</a>	English (for AU)	pdf	5485 KB
<a href="#">Quick Reference Guide</a>	English	pdf	443 KB
<a href="#">Instructional Video: User Guide</a>	English		KB

[Neem contact op](#) | [OmniMount TV Mounts](#) | [Anthro Tech Furniture](#) | [Sitemap](#) | [Gebruiksvoorwaarden en privacybeleid](#) | [Garantiebepalingen](#)  
Copyright 1996-2016 Ergotron, Inc. Alle rechten voorbehouden