



Intel S4500 Entry SATA 6Gb SSDs Product Guide

The Intel S4500 Entry SATA solid-state drives (SSDs) for Lenovo servers use Intel 3D NAND TLC Flash Memory technology with a 6Gbps SATA interface to provide an affordable solution with industry leading performance. Compared with the Intel S3520 series, these new drives offer improved performance and lower latency. The S4500 SSDs are optimized for read-intensive applications such as boot, web servers, lower data rate operational databases and analytics.



Figure 1. Intel S4500 Entry SATA SSD (without the hot-swap drive tray)

Did you know?

By combining the latest Intel 3D NAND TLC Flash Memory technology with Intel's latest controller technology, the design of the S4500 Entry SATA SSDs delivers consistent performance, reduced power consumption, and end-to-end data protection, as well as being optimized for IOPS/watt and cost/IOPS.

Rigorous testing of S4500 Entry SATA SSDs by Lenovo through the ServerProven program assures a high degree of storage subsystem compatibility and reliability. Providing additional peace of mind, these drives are covered under Lenovo warranty.

Part number information

The following table lists the ordering information for drives for ThinkSystem servers.

Table 1. Ordering information for ThinkSystem

Part number	Feature	Description
2.5-inch drives with hot-swap tray		
7SD7A05742	B0YY	ThinkSystem 2.5" Intel S4500 240GB Entry SATA 6Gb Hot Swap SSD
7SD7A05741	B0YZ	ThinkSystem 2.5" Intel S4500 480GB Entry SATA 6Gb Hot Swap SSD
7SD7A05740	B0Z0	ThinkSystem 2.5" Intel S4500 960GB Entry SATA 6Gb Hot Swap SSD
7SD7A05739	B0Z1	ThinkSystem 2.5" Intel S4500 1.92TB Entry SATA 6Gb Hot Swap SSD
7SD7A05738	B0Z2	ThinkSystem 2.5" Intel S4500 3.84TB Entry SATA 6Gb Hot Swap SSD
3.5-inch drives with hot-swap tray		
7SD7A05737	B0Z3	ThinkSystem 3.5" Intel S4500 240GB Entry SATA 6Gb Hot Swap SSD
7SD7A05736	B0Z4	ThinkSystem 3.5" Intel S4500 480GB Entry SATA 6Gb Hot Swap SSD
7SD7A05735	B0Z5	ThinkSystem 3.5" Intel S4500 960GB Entry SATA 6Gb Hot Swap SSD
7SD7A05734	B0Z6	ThinkSystem 3.5" Intel S4500 1.92TB Entry SATA 6Gb Hot Swap SSD
7SD7A05733	B0Z7	ThinkSystem 3.5" Intel S4500 3.84TB Entry SATA 6Gb Hot Swap SSD

The following table lists the ordering information for drives for System x, NeXtScale and Flex System servers.

Table 2. Ordering information for System x

Part number	Feature	Description
2.5-inch drives with G3HS hot-swap tray		
7SD7A05732	B0Z8	Intel S4500 240GB Enterprise Entry SATA G3HS 2.5" SSD
7SD7A05731	B0Z9	Intel S4500 480GB Enterprise Entry SATA G3HS 2.5" SSD
7SD7A05730	B0ZA	Intel S4500 960GB Enterprise Entry SATA G3HS 2.5" SSD
4XB7A08493	B0ZB	Intel S4500 1.92TB Enterprise Entry SATA G3HS 2.5" SSD
4XB7A08494	B0ZC	Intel S4500 3.84TB Enterprise Entry SATA G3HS 2.5" SSD
3.5-inch drives with hot-swap tray		
7SD7A05729	B0ZD	Intel S4500 240GB Enterprise Entry SATA HS 3.5" SSD
7SD7A05728	B0ZE	Intel S4500 480GB Enterprise Entry SATA HS 3.5" SSD
7SD7A05727	B0ZF	Intel S4500 960GB Enterprise Entry SATA HS 3.5" SSD
4XB7A08495	B0ZG	Intel S4500 1.92TB Enterprise Entry SATA HS 3.5" SSD
4XB7A08496	B0ZH	Intel S4500 3.84TB Enterprise Entry SATA HS 3.5" SSD
2.5-inch drives for NeXtScale		
7SD7A05726	B0ZJ	Intel S4500 240GB Enterprise Entry SATA 2.5" SSD for NeXtScale
7SD7A05725	B0ZK	Intel S4500 480GB Enterprise Entry SATA 2.5" SSD for NeXtScale
7SD7A05724	B0ZL	Intel S4500 960GB Enterprise Entry SATA 2.5" SSD for NeXtScale
4XB7A08497	B0ZM	Intel S4500 1.92TB Enterprise Entry SATA 2.5" SSD for NeXtScale
4XB7A08498	B0ZN	Intel S4500 3.84TB Enterprise Entry SATA 2.5" SSD for NeXtScale

Features

The Intel S4500 Entry SATA SSDs have the following features:

- Industry standard 2.5-inch or 3.5-inch form factors
- Cost-effective Intel 3D NAND TLC Flash Memory
- Endurance of 1 drive writes per day (DWPD) for 5 years, using Intel Standard Endurance Technology (SET). The total number of bytes that can be written to the drive (TBW) is as follows:
 - 240 GB drive: 620 TB
 - 480 GB drive: 900 TB
 - 960 GB drive: 1.86 PB
 - 1.92 TB drive: 3.27 PB
- SATA TLC solid-state drive with high read performance and consistently low latencies to fulfill client needs in the enterprise space
- High reliability and enhanced ruggedness
- Energy savings, with 5.6 W typical power consumption per drive
- Absence of moving parts to reduce potential failure points in the server
- S.M.A.R.T. support
- Advanced Encrypting Standard (AES) 256-bit encryption
- Full end-to-end data path protection
- Thermal throttling to extend the life of the drive
- Enhanced power loss data protection

SSDs have a huge but finite number of program/erase (P/E) cycles, which affect how long they can perform write operations and thus their life expectancy. Enterprise Entry SSDs typically have a better cost per read IOPS ratio but lower endurance and performance compared to Enterprise Performance SSDs. SSD write endurance is typically measured by the number of program/erase cycles that the drive can incur over its lifetime, which is listed as total bytes written (TBW) in the device specification.

The TBW value that is assigned to a solid-state device is the total bytes of written data that a drive can be guaranteed to complete. Reaching this limit does not cause the drive to immediately fail; the TBW simply denotes the maximum number of writes that can be guaranteed. A solid-state device does *not* fail upon reaching the specified TBW. However, at some point after surpassing the TBW value (and based on manufacturing variance margins), the drive reaches the end-of-life point, at which time the drive goes into read-only mode. Because of such behavior, careful planning must be done to use SSDs in the application environments to ensure that the TBW of the drive is not exceeded before the required life expectancy.

For example, the S4500 Entry 960 GB drive has an endurance of 1,860 TB of total bytes written (TBW). This means that for full operation over five years, write workload must be limited to no more than 1,019 GB of writes per day, which is equivalent to 1.1 full drive writes per day (DWPD). For the device to last three years, the drive write workload must be limited to no more than 1,699 GB of writes per day, which is equivalent to 1.8 full drive writes per day.

Technical specifications

The following table presents technical specifications for the Intel S4500 Entry SATA SSDs.

Table 3. Technical specifications

Feature	240 GB drive	480 GB drive	960 GB drive	1.92 TB drive	3.84 TB drive
Interface	6 Gbps SATA				
Capacity	240 GB	480 GB	960 GB	1.92 TB	3.84 TB
Endurance (drive writes per day)	1.42 DWPD	1.03 DWPD	1.06 DWPD	1.06 DWPD	1.09 DWPD
Endurance (total bytes written)	620 TB	900 TB	1.86 PB	3.27 PB	7.64 PB
Data reliability	< 1 in 10 ¹⁷ bits read				
MTBF	2,000,000 hours				
IOPS reads (4 KB blocks)	69,000	72,000	72,000	72,000	72,000
IOPS writes (4 KB blocks)	16,000	20,000	30,000	33,500	33,000
Sequential read rate (128 KB blocks)	500 MBps				
Sequential write rate (128 KB blocks)	190 MBps	330 MBps	490 MBps	490 MBps	470 MBps
Read latency (seq)	36 µs				
Write latency (seq)	36 µs				
Shock, operating	1,000 G (Max) at 0.5 ms				
Vibration, operating	2.17 G _{RMS} (5-700 Hz)				
Vibration, non-operating	3.13 G _{RMS} (5-800 Hz)				
Typical power (Active Write Avg)	2.6 W	3.6 W	4.8 W	5.0 W	5.6 W

Server support - ThinkSystem

The following table lists the ThinkSystem servers that are compatible.

Table 4. ThinkSystem server support

Part number	Description	2S Rack & Tower						4S Rack			Dense/ Blade			
		ST550 (7X09/7X10)	SR530 (7X07/7X08)	SR550 (7X03/7X04)	SR570 (7Y03/7Y04)	SR590 (7X98/7X99)	SR630 (7X01/7X02)	SR650 (7X05/7X06)	SR850 (7X18/7X19)	SR860 (7X69/7X70)	SR950 (7X11/12/13)	SD530 (7X21)	SN550 (7X16)	SN850 (7X15)
2.5-inch drives with hot-swap tray														
7SD7A05742	ThinkSystem 2.5" Intel S4500 240GB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	Y	N	N	Y	Y	Y
7SD7A05741	ThinkSystem 2.5" Intel S4500 480GB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	Y	N	N	Y	Y	Y
7SD7A05740	ThinkSystem 2.5" Intel S4500 960GB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	Y	N	N	Y	Y	Y
7SD7A05739	ThinkSystem 2.5" Intel S4500 1.92TB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	Y	N	N	Y	Y	Y
7SD7A05738	ThinkSystem 2.5" Intel S4500 3.84TB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	Y	N	N	Y	Y	Y
3.5-inch drives with hot-swap tray														
7SD7A05737	ThinkSystem 3.5" Intel S4500 240GB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	N	N	N	N	N	N
7SD7A05736	ThinkSystem 3.5" Intel S4500 480GB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	N	N	N	N	N	N
7SD7A05735	ThinkSystem 3.5" Intel S4500 960GB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	N	N	N	N	N	N
7SD7A05734	ThinkSystem 3.5" Intel S4500 1.92TB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	N	N	N	N	N	N
7SD7A05733	ThinkSystem 3.5" Intel S4500 3.84TB Entry SATA 6Gb Hot Swap SSD	Y	Y	Y	N	N	Y	Y	N	N	N	N	N	N

Server support - System x

The following tables list the System x servers that are compatible.

Support for System x and dense servers with Xeon E5/E7 v4 and E3 v5 processors

Table 5. Support for System x and dense servers with Xeon E5/E7 v4 and E3 v5 processors

Part number	Description	x3250 M6 (3943)	x3250 M6 (3633)	x3550 M5 (8869)	x3650 M5 (8871)	x3850 X6/x3950 X6 (6241, E7 v4)	nx360 M5 (5465, E5-2600 v4)	sd350 (5493)	nx360 M5 WCT (5467, E5-2600 v4)
2.5-inch drives with G3HS hot-swap tray									
7SD7A05732	Intel S4500 240GB Enterprise Entry SATA G3HS 2.5" SSD	Y	N	Y	Y	Y	Y	Y	N
7SD7A05731	Intel S4500 480GB Enterprise Entry SATA G3HS 2.5" SSD	Y	N	Y	Y	Y	Y	Y	N
7SD7A05730	Intel S4500 960GB Enterprise Entry SATA G3HS 2.5" SSD	Y	N	Y	Y	Y	Y	Y	N
4XB7A08493	Intel S4500 1.92TB Enterprise Entry SATA G3HS 2.5" SSD	Y	N	Y	Y	Y	Y	Y	N
4XB7A08494	Intel S4500 3.84TB Enterprise Entry SATA G3HS 2.5" SSD	Y	N	Y	Y	Y	Y	Y	N
3.5-inch drives with hot-swap tray									
7SD7A05729	Intel S4500 240GB Enterprise Entry SATA HS 3.5" SSD	Y	N	Y	Y	N	N	N	N
7SD7A05728	Intel S4500 480GB Enterprise Entry SATA HS 3.5" SSD	Y	N	Y	Y	N	N	N	N
7SD7A05727	Intel S4500 960GB Enterprise Entry SATA HS 3.5" SSD	Y	N	Y	Y	N	N	N	N
4XB7A08495	Intel S4500 1.92TB Enterprise Entry SATA HS 3.5" SSD	Y	N	Y	Y	N	N	N	N
4XB7A08496	Intel S4500 3.84TB Enterprise Entry SATA HS 3.5" SSD	Y	N	Y	Y	N	N	N	N
2.5-inch drives for NeXtScale									
7SD7A05726	Intel S4500 240GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	Y	N	Y
7SD7A05725	Intel S4500 480GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	Y	N	Y
7SD7A05724	Intel S4500 960GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	Y	N	Y
4XB7A08497	Intel S4500 1.92TB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	Y	N	Y
4XB7A08498	Intel S4500 3.84TB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	Y	N	Y

Support for System x and dense servers with Intel Xeon v3 processors

Table 6. Support for servers with Intel Xeon v3 processors

Part number	Description	x3100 M5 (5457)	x3250 M5 (5458)	x3500 M5 (5464)	x3550 M5 (5463)	x3650 M5 (5462)	x3850 X6/x3950 X6 (6241, E7 v3)	nx360 M5 (5465)
2.5-inch drives with G3HS hot-swap tray								
7SD7A05732	Intel S4500 240GB Enterprise Entry SATA G3HS 2.5" SSD	N	N	N	N	N	Y	Y
7SD7A05731	Intel S4500 480GB Enterprise Entry SATA G3HS 2.5" SSD	N	N	N	N	N	Y	Y
7SD7A05730	Intel S4500 960GB Enterprise Entry SATA G3HS 2.5" SSD	N	N	N	N	N	Y	Y
4XB7A08493	Intel S4500 1.92TB Enterprise Entry SATA G3HS 2.5" SSD	N	N	N	N	N	Y	Y
4XB7A08494	Intel S4500 3.84TB Enterprise Entry SATA G3HS 2.5" SSD	N	N	N	N	N	Y	Y
3.5-inch drives with hot-swap tray								
7SD7A05729	Intel S4500 240GB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N
7SD7A05728	Intel S4500 480GB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N
7SD7A05727	Intel S4500 960GB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N
4XB7A08495	Intel S4500 1.92TB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N
4XB7A08496	Intel S4500 3.84TB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N
2.5-inch drives for NeXtScale								
7SD7A05726	Intel S4500 240GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	Y
7SD7A05725	Intel S4500 480GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	Y
7SD7A05724	Intel S4500 960GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	Y
4XB7A08497	Intel S4500 1.92TB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	Y
4XB7A08498	Intel S4500 3.84TB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	Y

Server support - Flex System

The following table lists the compatibility information for Flex System servers.

Tip: For the ThinkSystem SN550 and SN850, see the [ThinkSystem table](#).

Table 7. Support for Flex System servers

Part number	Description	x240 (8737, E5-2600 v2)	x240 (7162)	x240 M5 (9532, E5 v3)	x240 M5 (9532, E5 v4)	x440 (7167)	x880/x480/x280 X6 (7903)	x280/x480/x880 X6 (7196)	Storage Expansion Node
7SD7A05732	Intel S4500 240GB Enterprise Entry SATA G3HS 2.5" SSD	N	N	Y	Y	N	N	N	N
7SD7A05731	Intel S4500 480GB Enterprise Entry SATA G3HS 2.5" SSD	N	N	Y	Y	N	N	N	N
7SD7A05730	Intel S4500 960GB Enterprise Entry SATA G3HS 2.5" SSD	N	N	Y	Y	N	N	N	N
4XB7A08493	Intel S4500 1.92TB Enterprise Entry SATA G3HS 2.5" SSD	N	N	Y	Y	N	N	N	N
4XB7A08494	Intel S4500 3.84TB Enterprise Entry SATA G3HS 2.5" SSD	N	N	Y	Y	N	N	N	N
7SD7A05729	Intel S4500 240GB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N	N
7SD7A05728	Intel S4500 480GB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N	N
7SD7A05727	Intel S4500 960GB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N	N
4XB7A08495	Intel S4500 1.92TB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N	N
4XB7A08496	Intel S4500 3.84TB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N	N
7SD7A05726	Intel S4500 240GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	N	N
7SD7A05725	Intel S4500 480GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	N	N
7SD7A05724	Intel S4500 960GB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	N	N
4XB7A08497	Intel S4500 1.92TB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	N	N
4XB7A08498	Intel S4500 3.84TB Enterprise Entry SATA 2.5" SSD for NeXtScale	N	N	N	N	N	N	N	N

Operating system support

SSDs operate transparently to users, storage systems, applications, databases, and operating systems.

Operating system support is based on the controller used to connect to the drives. Consult the controller product guide for more information:

- RAID controllers: <https://lenovopress.com/servers/options/raid>
- SAS HBAs: <https://lenovopress.com/servers/options/hba>

Warranty

The Intel S4500 Entry SATA SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the servers's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

Physical specifications

The drives have the following physical specifications (approximate, without the tray):

- Height: 7 mm (0.3 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 63 g (2.2 oz lb) (66 g for the 1.92 TB and 3.84 TB drives)

Shipping dimensions and weight - 2.5-inch drives (approximate, including the tray):

- Height: 63 mm (2.5 in.)
- Width: 174 mm (6.9 in.)
- Depth: 133 mm (5.2 in.)
- Weight: 434 g (1.0 lb)

Shipping dimensions and weight - 3.5-inch drives (approximate, including the tray):

- Height: 95 mm (3.7 in.)
- Width: 257 mm (10.1 in.)
- Depth: 193 mm (7.6 in.)
- Weight: 484 g (1.1 lb)

Operating environment

The SSDs are supported in the following environment:

- Temperature: 0 - 70°C (32 - 158°F)
- Relative humidity: 5 - 95% (noncondensing)
- Maximum altitude: 3,050 m (10,000 ft)

Agency approvals

The Intel S4500 Entry SATA SSDs conform to the following regulations:

- FCC Title 47, Part 15B, Class B
- CA/CSA-CEI/IEC CISPR 22:02
- EN 55024: 1998
- EN 55022: 2006
- EN-60950-1 2nd Edition
- UL/CSA EN-60950-1 2nd Edition
- Low Voltage Directive 2006/95/EC
- C-Tick: AS/NZS3584
- BSMI: CNS 13438
- KCC Article 11.1
- RoHS DIRECTIVE 2011/65/EU
- WEEE Directive 2002/96/EC

Related publications and links

For more information, see the following documents:

- Lenovo Enterprise SSD product page
<http://shop.lenovo.com/us/en/systems/servers/options/systemx/storage/solid-state/enterprise/>
- Intel SSD Data Center S4500 Series product page
<https://www.intel.com/content/www/us/en/products/memory-storage/solid-state-drives/data-center-ssds/dc-s4500-series.html>
- ServerProven for SSDs
<http://static.lenovo.com/us/en/serverproven/xseries/storage/hssdmatrix.shtml>
- Lenovo Press product guides for RAID controllers
<https://lenovopress.com/servers/options/raid>
- Lenovo RAID Introduction
<https://lenovopress.com/lp0578-lenovo-raid-introduction>
- Lenovo RAID Management Tools and Resources
<https://lenovopress.com/lp0579-lenovo-raid-management-tools-and-resources>

Related product families

Product families related to this document are the following:

- [Drives](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
1009 Think Place - Building One
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2017. All rights reserved.

This document, LP0755, was created or updated on September 12, 2017.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<http://lenovopress.com/LP0755>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <http://lenovopress.com/LP0755>.

Trademarks

Lenovo, the Lenovo logo, and For Those Who Do are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <http://www3.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Flex System

Lenovo®

NeXtScale

ServerProven®

System x®

ThinkSystem

The following terms are trademarks of other companies:

Intel and Xeon are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Other company, product, or service names may be trademarks or service marks of others.