

## Frequently applied accessories for projection screens

This page provides additional explanations on a number of the most frequently applied accessories. This information involves the accessories for electrical and manual projection screens. All of the accessories available for each product are shown separately on the relevant pages.

## Mounting materials



### Ceiling brackets

For installation of a projection screen in a high room or under a recessed ceiling, special ceiling brackets are available. The ceiling brackets measuring 100 cm (length) may be shortened as needed.

- 10800002 white
- 10800004 white
- 10800078 white
- 10800005 black
- 10800017 black



### Wall brackets

In certain cases, it is desirable to remove the projection screen from the wall. This may be the case for example if a painting is hanging where the projection screen will need to be mounted, or in the case of overhead projection, the projection screen fabric must be able to be placed under a corner to prevent a distortion of the image.

- 10800001
- 10800036



- 10800008



### Wall clamps

Using wall clamps, the projection screen fabric may be affixed under a corner. To do this, the slat bar may be easily clicked into the wall clamp.

- 10800006
- 10800007

Extra mounting materials	Ceiling brackets white		Ceiling brackets black	
	prod.code	length in cm	prod.code	length in cm
Elpro (RF) Electrol	10800004	100		
Cinelpro (RF) Electrol	10800004	100		
Cinelpro (RF) Electrol				10800017 100
Advantage (Deluxe) Electrol	10800004	100		
Compact (RF) Electrol	10800002	100		
Cinema (RF) Electrol	10800002	100		10800005 100
Elpro Large Electrol	10800004	100		
Master Electrol	10800078	100		
Hapro Manual	10800004	100		
Compact Manual	10800002	100		
ProScreen	10800002	100		
ProCinema	10800002	100		10800005 100
SlimScreen	10800002	100		
SlimCinema	10800002	100		10800005 100
SlimScreen XL				
FlexScreen	10800031	20	10800032	40-60

## Control materials



### Infrared remote control (IR)

The infrared-driven remote control comprises a wall box with an infrared receiver and transmitter. The wall box must be connected to the projection screen. The infrared receiver must be mounted in a visible location. Using the transmitter, the projection screen may be operated from a distance of up to 7 metres.

10800012



### Radio frequency remote control (RF)

The radio frequency remote control is a three-part set comprising a control module, a transmitter as well as a cordless wall switch. The control module must be connected to the projection screen. The cordless wall switch may be mounted onto the wall without the need for any cabling. The projection screen may be operated using both the wall switch as well as the transmitter from a distance of up to 30 metres.


10800013



### Key switch

The use of a key switch can be the ideal solution for preventing the unauthorised use of your electrical projection screen.

10800009



### Pull rod

If the projection screen with spring mechanism is mounted at heights greater than 2.5 metres, a pull rod can be a handy aid in the rolling of a projection screen. The length of the pull rod is 125 cm.

10800021

Extra mounting materials	Wall brackets white				Wall clamps prod.code
	prod.code	length in cm	prod.code	length in cm	
Elpro (RF) Electrol	10800001	75	10800041	30	10800006
Cinelpro (RF) Electrol					
Cinelpro (RF) Electrol					
Advantage (Deluxe) Electrol					
Compact (RF) Electrol	10800001	75	10800041	30	10800006
Cinema (RF) Electrol					
Elpro Large Electrol	10800008	40			10800007
Master Electrol	10800077	50			
Hapro Manual	10800001	75	10800041	30	10800006
Compact Manual	10800001	75	10800041	30	10800006
ProScreen	10800001	75	10800041	30	
ProCinema					
SlimScreen	10800036	57			
SlimCinema					
SlimScreen XL	10800035	57			
FlexScreen					